


DC ISO 9001:2015 Group		SUPPORT RING	Data Sheet No: DC/CJKC/004
			Revision: 00



Support Ring



Split Ring



Back Up Ring

Product Overview :-

Made from Pipes, these rings are used to bind the heavy under-sheath power cables which have just been joint using the Cable Jointing kit. Galvanized or Zinc Plated MS support ring, used in cable joints to improve the electrical contact between the cable armour and the joint case. It also protects the cable cores from being crushed by the clamping force of the armour clamp. These Rings are zinc plated or galvanized for better longevity.

Main Technical Indicators :-

	Support Ring	Back up Ring	Split Ring
Technical Drawing No.	DC/SR/001	DC/BR/001	DC/SPR/001
MS Zinc Plated (White)	SRZW	BRZW	Galvanized – SPGW
MS Zinc Plated (Yellow)	SRZY	BRZY	Galvanized – SPGY
Brass	SRBR	-	-
Aluminum	SRAL	-	SPAL
Diameter	Ranges from 19 to 105mm	Ranges from 54 to 105mm	Ranges from 26 to 115mm
Thickness	1.5 to 2mm	1.5 to 2mm	1/1.2/1.5 mm
Length	As per Customer Requirement		

We have a dedicated in house R & D to develop the Support Ring as per your technical requirement.